

# Yamwa Corporation

Floating type, 2 piece, high mounting Ball Valve by Yamwa Corporation maintainable low & high capacity type, YM30-ZF150, 300, 600 with WCB body & stainless steel ball, Handel Operated.



1/2" to 12"  
Class 150, 300, 600  
Flange End

## Materials:

1. Body Carbon Steel ASTM A-216 WCB
2. Cap Carbon Steel ASTM A-216 WCB
3. Ball Stainless Steel ASTM A-182 F316
4. Gasket PTFE
5. Seat Reinforced PTFE
6. Stem ASTM A-183 F6a
7. Packing PTFE
8. Gland ASTM A-182 F6a
9. Gland Flange ASTM A-216 WCB
10. Lever Carbon Steel  
(optional extra)

## YM30-ZF Floating Type Ball Valve Flanged

*Fire Safe Design  
& S.S Ball For  
Long Life .....*

## Description:

The YM30-ZF is floating type, 2 piece, high mounting ball valve flange ends. The YM30-ZF is specifically fire safe designed for Water, Oils, Gas, and therefore is ideal for low & high capacity Pipelines. The YM30-ZF ball valve is carbon steel body with stainless steel ball for long life.

Gear & Pneumatic Actuator type is also available.

## Applicable Standards:

Design	: ASME B16.34, API 608
Face to Face	: ASME B16.10
End Flange	: ASME B 16.34
Wall Thickness	: ASME B 16.5
Fire Safe	: API 607 4th 1993, BS 6755 Part 2
Inspections & Testing	: API 598, API 6D



**YAMWA CORPORATION**

Overseas Div. 648-9, Miyamae, Irukadeshinden, Komaki, 368, Japan Web: [www.yamwa.com](http://www.yamwa.com) E-mail: [sales@yamwa.com](mailto:sales@yamwa.com)