

Yamwa Corporation

Swing type, S.S Disc, high Pressure Check Valve, Flange Ends shall be Yamwa Corporation maintainable low & high capacity type, YM30-KF150, 300 & 600 with WCB body & stainless steel disc.



2" to 12"
Class 150, 300 & 600
Flange End

Materials:

1. Body Carbon Steel ASTM A-216 WCB
2. Seat Ring A-105 + 13Cr
3. Disc Stainless Steel ASTM A-351 CF8
4. Arm ASTM A-216 WCB
5. Nut ASTM A194 2H
6. Arm Pin ASTM A-182 F6a
7. Yoke ASTM A-216 WCB
8. Gasket 304 + Graphite
9. Bonnet ASTM A-216 WCB
10. Eye Bolt ASTM A-216 WCB
(optional extra)

YM30-KF

Swing Type Check Valve

*Flange End Design
& S.S Disc For
Long Life*

Description:

The YM30-KF is swing type with stainless steel disc, high pressure check valve flange ends. The YM30-KF is specifically for Water, Oils, Gas, and therefore is ideal for low & high capacity pipelines. The YM30-KF check valve is carbon steel body, with stainless steel disc for long life of product.

Wafer type is also available on demand.

Applicable Standards:

Design	: ASME B16.34, API 6D
Face to Face	: ASME B16.10
End Flange	: ASME B16.5, 16.47
Wall Thickness	: API 600 & BS1868
Pressure - Temperature	: ASME B16.34
Inspections & Testing	: API 598, API 6D



YAMWA CORPORATION