

Yamwa Corporation

Globe Valve, bellow sealed type, flange end, YM30-OF16 & 40
Throttling plug, Locking device with lubricating nipple,
Spindle protection cover for stroke limiter, Double wall bellow seal,
Bonnet made of tougher material

YM30-OF Bellow Sealed Globe Valve Flanged

*Quality maintained
throughout a
product life.....*

Description:

*The MY30-OF bellow sealed globe valve, DIN, flanged
The YM30-OF is specifically designed for Steam,
heat transfer oil, thermal oil, vapours, gases, hot or
domestic water, vacuum, ammonia & etc.....*

PN 16 upto 300 C PN 40 upto 425 C

In industry, process engineering, plant construction

*The YM30-OF globe valve is carbon steel body with
stainless steel bellow for product life.*

Technical Specification:

Design and manufacture : DIN EN 13709:2003

Face to face dimension : DIN EN 558-1:1995

End flange dimension : DIN EN 1092:2002

Inspection and test : DIN EN 12266:2003



**1/2" to 12"
PN16 & PN40 Flange End**

Materials:

1. Body : GS-C25(1.0619)
2. Disc : 1.1151
3. Pin : 1.4021
4. Stem : 1.4021
5. Bellow : 1.4301
6. Bonnet : GS-C25 (1.0619)
7. Packing : Flexible Graphite
8. Gland : 1.1181
9. Key : 1.1191
10. Hand Whaal : 1.1191
(optional extra)



YAMWA CORPORATION

Overseas Div. 648-9, Miyamae, Irukadeshinden, Komaki, 368, Japan Web: www.yamwa.com E-mail: sales@yamwa.com